



**PRODUCT INFO
& DATASHEET**

NPK 20-20-20 + CTE

HIGH PERFORMANCE (HP) water soluble crystalline fertiliser

- E.C. Fertiliser -

Recipe 20060201 Code nr. 11 - 03/04/2023

1/ PRODUCT SPECIFICATIONS

Typical chemical analysis			
Total Nitrogen	N	%	20.0
Nitric Nitrogen	N-NO ₃	%	6.0
Ammoniacal Nitrogen	N-NH ₄	%	3.9
Ureic Nitrogen	N-NH ₂	%	10.1
Phosphorus pentoxide, water soluble	P ₂ O ₅	%	20.0
Phosphorus pentoxide, soluble in neutral ammonium citrate and in water	P ₂ O ₅	%	20.0
Potassium oxide, water soluble	K ₂ O	%	20.0
Chelated trace elements			
Total Boron, soluble	B	%	0.010
Total Copper	Cu	%	0.008
Copper chelated by EDTA	Cu EDTA	%	0.008
Total Iron	Fe	%	0.026
Iron chelated by EDTA	Fe EDTA	%	0.026
Total Manganese	Mn	%	0.032
Manganese chelated by EDTA	Mn EDTA	%	0.032
Total Zinc	Zn	%	0.023
Zinc chelated by EDTA	Zn EDTA	%	0.023
Other parameters			
Low in chloride			
pH (1 %)		pH	4.6 +/- 0.3
Water soluble fertiliser			
Appearance			blue crystalline
pH range in which a good stability of the chelated fraction is guaranteed:			
Fe-EDTA pH		pH	1.5 - 6.5
Cu-EDTA, Mn-EDTA, Zn-EDTA		pH	3.5 - 10.0

2/ GENERAL RECOMMENDATIONS FOR USE

HP NPK's are fully water soluble fertilisers and hence suitable for fertirrigation and foliar applications.

As foliar fertiliser: use 2-6 kg/ha in 200-1000 litres of water. Apply when deficiency symptoms occur and repeat 2 - 3 times.

In fertigation: use 2 gr/l in irrigation water. Apply shortly before stage of strong growth and repeat the application.

The above recommendations should be adapted depending on differences in climate, soil temperature, application and irrigation system. Furthermore: the number of applications, the quantity per ha as well as the interval times may vary regarding the culture types and the formulations. Please consult your local dealer or a qualified agronomist.

3/ HOW TO APPLY ?

- Add HP NPK gradually to the water filled mixing tank, while stirring the solution.
- Solubility is affected by water temperature, which we recommend to be at 20 °C.
- In case of mixing different products with HP NPK, always add first HP NPK and other products afterwards.
- Do not mix with products based on calcium.
- When mixing with pesticides for the first time, test on a small scale before general use.
- For foliar feedings: apply during the coolest time of a hot day (in the evening) and the warmest time of a cool day ideally not in temperatures above 27 °C.
- Stir well before application
- Use not less than 400 litres of spray liquid per ha.
- In general, avoid application during flowering.

Any information in this publication is believed to be accurate and is given in good faith, but is for the customer to satisfy itself of the suitability for its own particular purpose.
No representation, warranty or guarantee is made to its accuracy, reliability or completeness.

SAP INTERNATIONAL CORPORATION bv Krekelenberg 83, B-2980 Zoersel, Belgium
Tel. +32-3-309.06.51 Email : info@sico.be Website : www.sico.be



- The use of wetting agents may improve effectiveness (please consult us). It is important to know the pH of the irrigation water. Our SICO PENETRATOR agricultural spraying water conditioner combats medium and high pH water and neutralises unwanted ions such as calcium, magnesium and bicarbonates. Please ask for our literature.

4/ STORAGE CONDITIONS

- Store dry & cool, away from direct sunlight, in well-ventilated warehouse & area.
- Highly soluble products are very hygroscopic: protect the products from humidity during handling & storage.
- Keep bags well closed, away from children.

5/ TOLERANCES AND DEVIATIONS ALLOWED AS PER EU REGULATIONS.

Methods of sampling and of analysis and analysis tolerances & deviations allowed as per E.C. regulations.

The E.C. methods of sampling & analysis, allowed tolerances & regulations etc. can be found on

internet http://ec.europa.eu/enterprise/chemicals/legislation/fertilizers/index_en.htm. Also tolerances on analysis are as per regulation (EC) nr. 2003/2003 of the European Parliament and of the Council of 13 October 2003 relating to fertilisers.

Before using this product, please read the product specifications, the material safety datasheet and any other applicable product literature. The conditions of your use and application of our products, technical assistance and information (whether verbal, written, or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended use and applications. Such application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoints. It is also not recommended that the product be used for any described purpose without verification by the user of compliance with all applicable laws, regulations and registration requirements. No warranty is made as to the accuracy of any data or statements contained herein other than the chemical specifications guaranteed in this Product Datasheet. While this product is furnished in good faith, this product is provided to you without any representation or warranty, expressed or implied, as to condition, utility, merchantability, completeness, suitability or fitness for any particular purpose or use or any other matter or thing whatsoever and without recourse against Sap Int. Corp. and in any event. Without limiting the generality of the foregoing. SAP Int. Corp. specifically disclaims any responsibility or liability to the use of this product and shall not in any event, be liable for any special, incidental or consequential damages arising from such use. See also our general conditions of sale on our website www.sico.be